



VA 35 SH

Electric

Article code	Power	Wattage / HP
800112	3 × 400 V, 50 HZ	11 Kw / 15HP
800193	3 × 480 V, 60 HZ	12.6 Kw / 17HP

Key features	
Working width	35 cm / 14"
Distance to wall	14 cm / 5.5"
Depth hard concrete	8 mm / .31"
Depth regular concrete	11 mm / .43"
Production / h	60-65 m ² / 700 sqf
Standard cutters	Octagonal carbide

Physical parameters	
Weight kg / lbs	346 / 763
Dimensions mm / inch	681x1395x1014 / 27x55x40

Pairing with	
T7 dust extractor	T8 dust extractor

Field of application	
<p>Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:</p> <ul style="list-style-type: none"> • Asphalt and cast asphalt surfaces • Concrete and cement, synthetic stone, floor tiles • Screeds of cement, wood cement, ceramic etc. • Natural stone • Metals • Thermoplastic materials 	
<p>Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:</p> <ul style="list-style-type: none"> • Latex, rubber, soft plastics and foam materials • Wood, carpets and woven materials 	

SPARE PARTS

Octagonal cutters for VA 35 SH	Octagonal cutters set 800198		Complete drum 600312		Application: With tungsten carbide inserts, for roughening concrete and asphalt, for removing old coatings One set contains: 4 flail shafts, 124 washers, 80 pcs octagonal cutters large
---------------------------------------	--	---	--------------------------------	---	---