



MODEL	L25RS7
Power	15 hp / 11 kW
Voltage (50-60 Hz) High Voltge Version	3 phase, 200-240V, 45A 3 phase, 400-480V, 30A
EU MODEL	3ph, 380-400V, 30A (max)
Dedicated Breaker	45 Amp
Weight of Machine	1135 lbs / 515 kg
Grinding Pressure	463-624 lbs / 210-283 kg
Tool Holder RPM	400-1100 rpm
Working Width	26.5 in / 673 mm
Tool Holders (Left Rotation)	3x9 in / 3x225 mm
Vacuum Hose Port	Camlock E250
Water Feed	tank or hose connection
Water Tank	5.2 gal / 20 L
Transport Wheel	yes
Cable Length	57 ft / 17.4 m
Machine Size L x W x H	84 x 29 x 46 in 214 x 72 x 116 cm

L25RS7

NEW REMOTE-CONTROLLED 25" S7 GRINDER





GRIND AND POLISH WITH EASE.

- New user-friendly remote control for precise operation and improved productivity
- New frame design with updated weights and handle for better operator experience
- Sealed and dust-proof grinding head with upgraded internals for longer service life
- Transport wheel for easy loading and transportation is included.











- ✓ Remote control with 4.3" TFT LCD display
- ✓ Removable Li-Ion battery with battery charger
- ✓ M-Key removable magnetic power key switch
- Controls include: emergency stop, two joysticks for grinder movement, switches for engine rpm, direction of tool rotation, speed rpm, swing correction
- Main screen to monitor working parameters power supply voltage and battery condition, engine load and RPMs, Amps consumption and rotation direction of tools, maintenance alerts, job hours, etc.