

BETON TROWEL

CONCRETE FINISHING
& COMPACTION



RIDE ON POWER TROWEL BT1200DTC

New BT Diesel Rider with
Yanmar 44 HP EU stage V and
USA tier IV Final Low
Emissions



- Heavy Duty reduction gearboxes with Helical gears and higher speed ratio (24 month Warranty)
- Driven by CVT Clutch for instant power transmission giving slow speed High torque power for using Float Pans and giving high speed finishing to 195 RPM
- Hydraulic blade pitch for no effort fingertip control of the blade pitch
- Hydraulic steering for no effort fingertip control of the machine
- 4 x Running Lights as standard
- Seat adjuster standard
- Water spray system, drink holder and engine hour meter standard
- Economic running costs of Diesel vs Petrol.
- 5 Blade spider assembly's for stability and fast closing of floor on final finishing. Spider machining is precision tolerance fit for the trowel arms therefore minimising wear and ensuring long service life
- Fork pockets for easy loading
- Grease points at spider to ensure continual free movement of blade pitch.
- Good all round visibility of blades and concrete for the operator
- Optional 2 wheel transporter for site use and blade changing

SPECIFICATIONS:

- Dimensions: 2540mm x 1270mm x 1360mm
- Weight: 825 kg
- Blade: RPM 195
- Blade Types: Finish, Combination, wide finish
- Pan type: five blade pan with security pins