

ULTRALIT CLEAN

MAINTENANCE HARDENING CLEANER FOR AUTOSCRUBBERS

DESCRIPTION

ULTRALIT CLEAN effectively removes general dirt as well as grease and oil common in assembly shops and garages of the motor vehicle and metal industry as well as on any industrial flooring. Both when manually and mechanically applied, Ultralit Clean offers excellent reticulation properties and is low foaming. ULTRALIT CLEAN is free from phosphate, chlorine, complexing agents and silicone, and therefore corresponds to environmental protection standards. Having small content of active lithium inside, constantly hardens and dustproofs Your floor.

CAN BE APPLIED ON

Suitable for use on all alkali-resistant and water-resistant industrial floors, such as concrete, cementitious screed, hard baked brick, clay floor tiles "cotto", stoneware tiles, epoxy resin floors and asphalt slabs. Not suitable for linoleum or rubber floors!

PHYSICAL PROPERTIES

pH value (concentrate): approx. 12

pH value (ready-to-use solution) approx. 10

PACKAGING



Ultralit CLEAN
is packed in
10, 20 liter cans

COVERAGE RATES

Wiping / mechanical wet cleaning: 1-2 mL/m²

Intensive cleaning: 2-5 mL/m²

APPLICATION

- Routine cleaning (wiping / mechanical wet cleaning): Dilute 100-200 mL in 10 litres of cold water, depending on the degree of dirt.
- Intensive cleaning: Dilute 200-500 mL in 10 litres of cold water, depending on the degree of dirt. Distribute the cleaning solution, scrub, vacuum and rinse with clear water.

SAFETY / HEALTH INFORMATION

Before using or handling this material, read the Material Safety Data Sheet. Eye, skin and gastrointestinal tract and respiratory tract irritant. Avoid contact with eyes, skin and clothing. Keep out of reach of children. Do not take internally.

CUSTOMER SUPPORT

ULTRALIT CLEAN is available worldwide. For technical assistance, product information, Dealer location - visit our web site at www.ultralit.eu or email at info@ultralit.eu.