



L30S7

S7 SERIES



MODEL	L30S7
Power	15 hp / 11 kW
Voltage (50-60Hz)	3 phase, 200-240V, 45A
Also in High Voltage	3 phase, 400-480V, 30A
Dedicated Breaker	45 Amp
Weight of Machine	998 lbs / 453 kg
Grinding Pressure (integrated weights)	460-619 lbs 209-289 kg
Tool Holder RPM	400-765 rpm
Working Width	30.8 in / 783 mm
Tool Holder Diameter	3x13.2in / 3x335mm
Vacuum Hose Port	Camlock E300
Water Feed	tank or hose connection
Water Tank	5.2 gal / 20 L
Cable Length	57 ft / 17.4 m
Machine Size L x W x H	85 x 32 x 46 in 216 x 82 x 116 cm



L30S7 FEATURES

SEALED, DUST-PROOF GRINDING HEAD FOR LONGER SERVICE LIFE

- Completely redesigned chain-driven planetary drive
- New stronger timing belt.
- Upgraded shafts, seals and bearings.
- New lighter timing pulleys for better power transmission.
- New 2-piece aluminum main belt housing with belt inspection cover for longer belt life and less maintenance.



ALL-NEW FRAME DESIGN AND FEATURES CONTRACTORS WILL LOVE

- New weights for faster position change.
- Redesigned frame allowing easier tool changes.
- New handle design – faster adjustability & more positions.
- Rubber bushing at head attachment points for less vibrations.
- New, heavy duty rubber tires.
- Adjustable LED lights with magnetic attachment.



OPTIONAL ACCESSORY:
TRANSPORT WHEEL

